

**METHOD AND APPARATUS FOR GENERATING GAMMA CORRECTED  
ANTIALIASED LINES**

**BACKGROUND OF THE INVENTION**

5   **1.    Technical Field:**

          The present invention relates generally to an improved data processing system and in particular to a method and apparatus for processing data. Still more particularly, the present invention provides a method and  
10   apparatus for processing graphics data.

**2.    Description of Related Art:**

          Data processing systems, such as personal computers and work stations, are commonly utilized to run  
15   computer-aided design (CAD) applications, computer-aided manufacturing (CAM) applications, and computer-aided software engineering (CASE) tools. Engineers, scientists, technicians, and others employ these applications daily. These applications involve complex  
20   calculations, such as finite element analysis, to model stress in structures. Often, modeling of these complex structures requires computer generated surfaces and lines that describe the features of physical models. Other applications include chemical or molecular modeling  
25   applications. CAD/CAM/CASE applications are normally graphics intensive in terms of the information relayed to the user. Data processing system users may employ other graphics intensive applications, such as desktop publishing applications. Generally, users of these  
30   applications require and demand that the data processing systems be able to provide extremely fast graphics information.

The processing of a graphics data stream to provide a graphical display on a video display terminal requires an extremely fast graphics system to provide a display with a rapid response. In these types of graphics systems, primitives are received for processing and display. A primitive is a graphics element that is used as a building block for creating images, such as, for example, a point, a line, a polygon, or text. A primitive is defined by a group of one or more vertices. A vertex defines a point, an end point of an line, or a corner of a polygon where two lines intersect. Data also is associated with a vertex in which the data includes information, such as positional coordinates, colors, normals, and texture coordinates. Commands are sent to the graphics system to define how the primitives and other data should be processed for display.

When lines are displayed on a display screen, a "stair stepping" or "jagged" appearance may be seen depending on the resolution of the display. This visual artifact is a manifestation of a sampling error called aliasing. Graphics adapters typically support a gamma adjustment on a screen or window basis that lightens or darkens the contents of the entire screen or window. Antialiasing techniques are implemented for smoothing or correcting this artifact. These techniques typically specify gradations in intensity of neighboring pixels near the edges of primitives, rather than setting pixels to maximum or zero intensity. These techniques essentially blur the lines by strategically adding pixels with a lower color intensity along the mathematical center of the line. As a result, lines normally one pixel in width are rendered as two or more pixel width

lines. These techniques tend to dampen or dilute the intended color intensity for the lines.

Therefore, it would be advantageous to have an improved method and apparatus for correcting artifacts or  
5 aliasing in text, points, lines, or triangles.

**SUMMARY OF THE INVENTION**

5       The present invention provides an improved method,  
apparatus, and computer implemented instructions for  
generating antialiased lines for display in a data  
processing system. This technique also may be applied to  
other primitives for other images, such as points,  
10 polygons, and text. Graphics data is received for  
display, wherein the graphics data includes primitives.  
A gamma correction is applied to the graphics data on a  
per primitive basis to form an antialiased line. In  
other words, only pixels generated for the line are  
15 adjusted. The gamma-corrected antialiased line is  
displayed.

**BRIEF DESCRIPTION OF THE DRAWINGS**

The novel features believed characteristic of the invention are set forth in the appended claims. The invention itself, however, as well as a preferred mode of use, further objectives and advantages thereof, will best be understood by reference to the following detailed description of an illustrative embodiment when read in conjunction with the accompanying drawings, wherein:

**Figure 1** is a pictorial representation of a data processing system in which the present invention may be implemented in accordance with a preferred embodiment of the present invention;

**Figure 2** is a block diagram of a data processing system in which the present invention may be implemented;

**Figure 3** is a diagram illustrating data flow for displaying graphics in accordance with a preferred embodiment of the present invention;

**Figure 4** is a flowchart of a process used for selecting a gamma table or a gamma function in accordance with a preferred embodiment of the present invention;

**Figure 5** is a flowchart of a process used for generating graphics data in accordance with a preferred embodiment of the present invention;

**Figure 6** is a flowchart of a process used for receiving a gamma correction table or a gamma correction function in accordance with a preferred embodiment of the present invention;

**Figure 7** is a flowchart of a process used for rasterizing a line in accordance with a preferred embodiment of the present invention;

Docket No. AUS920010010US1

**Figure 8** is a flowchart of a process used for generating a gamma correction table in accordance with a preferred embodiment of the present invention;

**Figure 9** is a block diagram illustrating a gamma correction mechanism in accordance with a preferred embodiment of the present invention;

**Figures 10A-10B** are code illustrating a process for generating a gamma correction table in accordance with a preferred embodiment of the present invention; and

**Figure 11** is code illustrating a more generalized version of the process illustrated in **Figures 10A-10B**.

**DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT**

With reference now to the figures and in particular  
5 with reference to **Figure 1**, a pictorial representation of  
a data processing system in which the present invention  
may be implemented is depicted in accordance with a  
preferred embodiment of the present invention. A  
computer **100** is depicted which includes a system unit  
10 **110**, a video display terminal **102**, a keyboard **104**,  
storage devices **108**, which may include floppy drives and  
other types of permanent and removable storage media, and  
mouse **106**. Additional input devices may be included with  
personal computer **100**, such as, for example, a joystick,  
15 touchpad, touch screen, trackball, microphone, and the  
like. Computer **100** can be implemented using any suitable  
computer, such as an IBM RS/6000 computer or  
IntelliStation computer, which are products of  
International Business Machines Corporation, located in  
20 Armonk, New York. Although the depicted representation  
shows a computer, other embodiments of the present  
invention may be implemented in other types of data  
processing systems, such as a network computer. Computer  
**100** also preferably includes a graphical user interface  
25 that may be implemented by means of systems software  
residing in computer readable media in operation within  
computer **100**.

With reference now to **Figure 2**, a block diagram of a  
data processing system is shown in which the present  
30 invention may be implemented. Data processing system **200**  
is an example of a computer, such as computer **100** in

**Figure 1**, in which code or instructions implementing the processes of the present invention may be located. Data processing system **200** employs a peripheral component interconnect (PCI) local bus architecture. Although the depicted example employs a PCI bus, other bus architectures such as Accelerated Graphics Port (AGP) and Industry Standard Architecture (ISA) may be used. Processor **202** and main memory **204** are connected to PCI bus **206** through PCI bridge **208**. PCI bridge **208** also may include an integrated memory controller and cache memory for processor **202**. Additional connections to PCI bus **206** may be made through direct component interconnection or through add-in boards. In the depicted example, local area network (LAN) adapter **210**, small computer system interface SCSI host bus adapter **212**, and expansion bus interface **214** are connected to PCI local bus **206** by direct component connection. In contrast, audio adapter **216**, graphics adapter **218**, and audio/video adapter **219** are connected to PCI local bus **206** by add-in boards inserted into expansion slots. Expansion bus interface **214** provides a connection for a keyboard and mouse adapter **220**, modem **222**, and additional memory **224**. SCSI host bus adapter **212** provides a connection for hard disk drive **226**, tape drive **228**, and CD-ROM drive **230**. Typical PCI local bus implementations will support three or four PCI expansion slots or add-in connectors.

An operating system runs on processor **202** and is used to coordinate and provide control of various components within data processing system **200** in **Figure 2**. The operating system may be a commercially available operating system such as Windows 2000, which is available from



Microsoft Corporation. An object oriented programming system such as Java may run in conjunction with the operating system and provides calls to the operating system from Java programs or applications executing on data processing system 200. "Java" is a trademark of Sun Microsystems, Inc. Instructions for the operating system, the object-oriented programming system, and applications or programs are located on storage devices, such as hard disk drive 226, and may be loaded into main memory 204 for execution by processor 202.

Those of ordinary skill in the art will appreciate that the hardware in **Figure 2** may vary depending on the implementation. Other internal hardware or peripheral devices, such as flash ROM (or equivalent nonvolatile memory) or optical disk drives and the like, may be used in addition to or in place of the hardware depicted in **Figure 2**. Also, the processes of the present invention may be applied to a multiprocessor data processing system.

For example, data processing system 200, if optionally configured as a network computer, may not include SCSI host bus adapter 212, hard disk drive 226, tape drive 228, and CD-ROM 230, as noted by dotted line 232 in **Figure 2** denoting optional inclusion. In that case, the computer, to be properly called a client computer, must include some type of network communication interface, such as LAN adapter 210, modem 222, or the like. As another example, data processing system 200 may be a stand-alone system configured to be bootable without relying on some type of network communication interface, whether or not data processing system 200 comprises some type of network communication interface. As a further

example, data processing system **200** may be a personal digital assistant (PDA), which is configured with ROM and/or flash ROM to provide nonvolatile memory for storing operating system files and/or user-generated data.

The depicted example in **Figure 2** and above-described examples are not meant to imply architectural limitations. For example, data processing system **200** also may be a notebook computer or hand held computer in addition to taking the form of a PDA. Data processing system **200** also may be a kiosk or a Web appliance.

The processes of the present invention are performed by processor **202** using computer implemented instructions, which may be located in a memory such as, for example, main memory **204**, memory **224**, or in one or more peripheral devices **226-230**.

The present invention provides a method, apparatus, and computer implemented instructions for generating gamma corrected antialiased lines. The mechanism of the present invention employs a gamma table or a gamma function, which may be applied to the pixels for the line. The adjustment is actually made to a fragment, which contains all the information used to display a pixel, such as color, intensity, and opacity.

Turning next to **Figure 3**, a diagram illustrating data flow for displaying graphics is depicted in accordance with a preferred embodiment of the present invention.

Host **300** contains application **302**. Graphics adapter **304** includes memory **306**, rasterization engine **308**, and frame buffer **310**. Graphics adapter **304** may be implemented in graphics adapter **218** in **Figure 2**. Host

**300** is implemented as other components within data processing system **200** in **Figure 2**, such as processor **202** and main memory **204** in **Figure 2**.

Application **302** generates graphics data to be  
5 displayed by graphics adapter **304**. Application **302** will send lines or other primitive to rasterization engine **308** for display. In these examples, rasterization engine **308** contains the hardware and/or software used by rasterization engine **308** to generate an image for display.  
10 Rasterization engine **308** is used to turn text and images into a matrix of pixels to form a bit map for display on a screen. If application **302** sets a gamma table or a gamma function, this table or function will be sent to memory **306** in graphics adapter **304**. In this example, memory **306**  
15 contains table **312** and function **314**, both of which may be used for performing gamma correction on the lines in a pixel by pixel basis. Lines received by rasterization engine **308** for display are processed to generated fragments. A fragment contains information about a  
20 pixel, such as color, position, depth information, and opacity.

Rasterization engine **308** will use information from table **312** or function **314** to generate a gamma correction for the pixel represented by the fragment. If table **312**  
25 is used, the primitive's pixel coverage value is used as an index into this table. If function **314** is used, then the fragment color is used to fill input variables in the function. For example, the function may take the form of an equation with values for red, green, and blue  
30 associated with the pixel being used as input values. The gamma corrected fragment is then sent to frame buffer

310 for display. The mechanism of the present invention avoids the color intensity dampening that occurs with presently available techniques by applying gamma corrections only to the pixels generated for the line by rasterization engine 308.

A variety of different tables may be specified by the application and stored within memory 306 in graphic adapter 304 with each table using a different gamma factor. These tables are generated at an application level, such as by application 302 and sent to graphics adapter 304. Alternatively, a function, such as a gamma correction equation is sent to graphic adapter 304. In this situation, the gamma correction applied to a fragment is calculated by the adapter. These calculations may be performed, for example, by software running on the graphics adapters processor or by hardware containing logic functions.

Turning next to **Figure 4**, a flowchart of a process used for selecting a gamma table or a gamma function is depicted in accordance with a preferred embodiment of the present invention. The process illustrated in **Figure 4** may be implemented in application 302 in **Figure 3**.

The process begins with the execution of application processes (step 400). These application processes include, for example, receiving user input, generating primitives for display, and performing input/output functions. Next, a determination is made as to whether the processes set a gamma table or a gamma function (step 402). The setting of a gamma table involves generating values for the table. In the depicted examples, the setting of the gamma function comprises selecting or generating an equation for use in obtaining gamma values

based on inputs, such as color. If set, the gamma table or gamma function is set, the table or function is sent to the adapter (step **404**) with the process terminating thereafter.

- 5       With reference again to step **402**, if not set, the process returns to step **400** to continue executing application processes.

Turning next to **Figure 5**, a flowchart of a process used for generating graphics data is depicted in  
10 accordance with a preferred embodiment of the present invention. The process illustrated in **Figure 5** may be implemented within application **302** in **Figure 3**.

The process begins with the execution of application processes (step **500**). Next, a determination is made as  
15 to whether a line is generated (step **502**). If a line is generated, the line is sent to the adapter (step **504**) with the process terminating thereafter.

With reference again to step **502**, if a line is not generated, the process returns to step **500**.

20       Turning next to **Figure 6**, a flowchart of a process used for receiving a gamma correction table or a gamma correction function is depicted in accordance with a preferred embodiment of the present invention. The process illustrated in **Figure 6** may be implemented in  
25 graphic adapter **304** in **Figure 3**.

The process begins by receiving a gamma correction table or a gamma correction function from an application (step **600**). Next, the table or function is stored in adapter storage (step **602**) with the process terminating  
30 thereafter. In the depicted examples, the table or function is stored in memory **306** in **Figure 3**.

Turning next to **Figure 7**, a flowchart of a process used for rasterizing a line is depicted in accordance with a preferred embodiment of the present invention. The process illustrated in **Figure 7** may be implemented in  
5 rasterization engine **308** in **Figure 3**.

The process begins by receiving a line from an application (step **700**). Next, the line is rasterized to generate fragments (step **702**). A determination is made as to whether a fragment is valid (step **704**). In  
10 determining whether the fragment is valid, identifications, such as, for example, as to whether the fragment is within the display window, whether the fragment is hidden by an object, and whether the object is within a stencil boundary are made. If the fragment  
15 is valid, a gamma correction is read from the gamma correction table or is generated from the gamma correction function (step **706**). The fragment is written to color buffer including the correction to the gamma value for the fragment (step **708**). A determination is  
20 made as to whether the line is finished (step **710**). If the line is finished, the process terminates.

With reference again to step **704**, if the fragment is not valid, the process proceeds to step **710**. With reference again to step **710**, if the line is not finished,  
25 the process returns to step **702**.

Turning next to **Figure 8**, a flowchart of a process used for generating a gamma correction table is depicted in accordance with a preferred embodiment of the present invention. The process illustrated in **Figure 8** may be  
30 implemented in application **302** in **Figure 3**.

The process begins by determining whether the entries in the table are to be gamma filtered (step 800). If the entries are to be gamma filtered, values for gamma, sum, width, and size are loaded or assigned default values (step 802). Then, the variable factor is set equal to  $2^{(8-\text{width})}$  (step 804). The index  $i$  equal to 0 (step 806).

Then, a determination is made as to whether  $i$  is less than 256 (step 808). If  $i$  is not less than 256, the process terminates. Otherwise, the value for Val is set as follows:

$$Val = (factor) \left[ \left( \frac{size}{256(factor)} \sum_{j=i}^{i+size-1} \left[ (sum) \left( \frac{j}{256} \right) \frac{1}{gamma} \right] \right) + .5 \right]$$

15

Where: Factor is an adjustment to the maximum value represent able by each table element, Sum = maximum intensity value that can be represented, may be less than maximum element value, but not more, Size is a number of entries in table where 256 is the maximum, and Width is a number of bits allocated per entry where 8 is the maximum (step 810). Then table entries  $i$  through  $i+size-1$  are set equal to the variable Val (step 812). The index  $i$  is then incremented by 1 (step 814) with the process then returning to step 808 as described above.

25

With reference again to step 800, if the entries are not to be gamma filtered, an index  $i$  is set equal to 0 (step 816). Then, a determination is made as to whether  $i$  is less than 256 (step 818). If  $i$  is not less than 256, the process terminates. Otherwise, table entry  $i$  is set equal to  $i$  (step 820). Next, the index  $i$  is

30

incremented by 1 (step 822) with the process then returning to step 818 as described above.

Turning next to **Figure 9**, a block diagram illustrating a gamma correction mechanism is depicted in accordance with a preferred embodiment of the present invention. The mechanism illustrated in **Figure 9** may be implemented in hardware within graphics adapter 304 in **Figure 3**.

Gamma correction unit 900 includes coverage interpolation unit 902, alpha interpolation unit 904, color interpolation 906, clamp 908, modulate function 910, blend function 912, gamma correction lookup table 914, and frame buffer 916. In these examples, coverage interpolation unit 902, alpha interpolation unit 904, color interpolation 906, clamp 908, modulate function 910, and blend function 912 may be located within rasterization engine 308 in **Figure 3**. Gamma correction lookup table 914 may be located within memory 306 in **Figure 3**. Frame buffer 916 is implemented as frame buffer 310 in **Figure 3**.

Coverage interpolation unit 902 identifies how much of a pixel is covered by a line. The pixel may be partially covered, entirely covered, or not covered at all by a line. Alpha interpolation unit 904 identifies a degree of transparency for the pixel. Color interpolation unit 906 interpolates or generates a red, green, and blue (RGB) value for the pixel. Clamp 908 prevents coverage values generated by coverage interpolation unit 902 from going out of a selected range of values.



The alpha value generated by alpha interpolation unit **904** is input into modulate function **910** along with a corrected gamma value from gamma correction lookup table **914**. Modulate function **910** functions to adjust the gamma correction factor by the opacity factor specified as the alpha component of the fragment. Blend unit **912** receives a frame buffer color from frame buffer **916**, a color value from color interpretation unit **906**, and a value from modulate function **910** to generate a final pixel value. This final pixel value is also referred to as a final fragment value. Blend unit **912** takes the values from modulate function **910** and color interpolation unit **912** and blends these values with the color value presently located in frame buffer **916**. This color value is the color value for the particular fragment.

Turning next to **Figures 10A-10B**, code illustrating a process for generating a gamma correction table are depicted in accordance with a preferred embodiment of the present invention. Code **1000** is an example of code embodying the process illustrated in **Figure 8**. Code **1000** is written in C language in these examples. A generalization of this algorithm that removes the assumptions regarding size of coverage values, number of table entries and power-of-2 limitations can be seen in code **1100** in **Figure 11**.

Thus, the present invention provides an improved method, apparatus, and computer implemented instructions for generating gamma corrected antialiased lines. The mechanism of the present invention avoids the color intensity dampening that occurs with presently available techniques by applying gamma corrections only to the

pixels generated for the line by the rasterization engine. Further, since the bulk of computational intensity is associated with the generation of pixel locations, the adjustment of pixel color intensity does not impact the overall rendering performance of a graphic adapter.

It is important to note that while the present invention has been described in the context of a fully functioning data processing system, those of ordinary skill in the art will appreciate that the processes of the present invention are capable of being distributed in the form of a computer readable medium of instructions and a variety of forms and that the present invention applies equally regardless of the particular type of signal bearing media actually used to carry out the distribution. Examples of computer readable media include recordable-type media, such as a floppy disk, a hard disk drive, a RAM, CD-ROMs, DVD-ROMs, and transmission-type media, such as digital and analog communications links, wired or wireless communications links using transmission forms, such as, for example, radio frequency and light wave transmissions. The computer readable media may take the form of coded formats that are decoded for actual use in a particular data processing system.

The description of the present invention has been presented for purposes of illustration and description, and is not intended to be exhaustive or limited to the invention in the form disclosed. Many modifications and variations will be apparent to those of ordinary skill in the art. The embodiment was chosen and described in order to best explain the principles of the invention,

Docket No. AUS920010010US1

the practical application, and to enable others of ordinary skill in the art to understand the invention for various embodiments with various modifications as are suited to the particular use contemplated.